


K-Series

General Purpose, 1-stage, medium attenuation

12704 W. Arden Place
Butler, WI 53007 USA
Phone: 262-790-0092
Fax: 262-790-0095
Website: www.emissioncontrol.com
E-mail: info@emissioncontrol.com

Part Number System



Agency Approvals:



Part Number	Current Rating Amps	Schematic
K20Q	20	
K20W	20	
K20S	20	

Electrical Specs

Rated Voltage: 250VAC 50/60 Hz.
Rated Current: @ 40° C

Hipot Rating:
Line to Ground: 1800 VAC, 2 sec.
Line to Line: 1700 VDC, 2 sec.

Climatic Category: HPF (25/085/21)

Maximum leakage current:
each line to ground
@ 250 VAC 50 Hz .23ma

Minimum insertion loss — dB (50 ohm circuit)

Current Rating	Mode	Frequency - MHZ						
		.05	.15	.5	1	5	10	30
20	Common	9	19	27	29	32	36	47
	Differential	7	15	12	40	65	61	57

* Low leakage medical versions
Available to meet UL544

Mechanical Specs

Construction: Metal case and cover. Internal components and terminations sealed with self-extinguishing resin.

Connections:

- S = Studs
M4
- Q = Quick-Connects
.25"(6.3)x.03"(0.8)
- W = Wire Leads
AWG 14

Dimensions: inches
(mm)

