

## L-Series

Printed Circuit, 1-stage, low cost

12704 W. Arden Place

Butler, WI 53007 USA


Phone: 262-790-0092

Fax: 262-790-0095

Website: www.emissioncontrol.com

E-mail: info@emissioncontrol.com

### Part Number System



Agency Approvals:



Part Number	Current Rating Amps	Schematic
L1P	1	<div style="display: flex; justify-content: space-between;"> <span>LINE</span> <span>LOAD</span> </div>
L3P	3	
L6P	6	

### Electrical Specs

Rated Voltage: 250VAC 50/60 Hz.

Rated Current: @ 40° C

Hipot Rating:

Line to Ground: 1800 VAC, 2 sec.

Line to Line: 1700 VDC, 2 sec.

Climatic Category: HPF (25/085/21)

Maximum leakage current:

each line to ground

@ 250 VAC 50 Hz .26ma

\* Low leakage medical versions

Available to meet UL544

Minimum insertion loss — dB (50 ohm circuit)

Current Rating	Mode	Frequency - MHZ							
		.01	.05	.15	.5	1	5	10	30
1	Common	21	34	44	48	47	45	52	27
	Differential	--	--	3	17	31	57	62	55
3	Common	9	22	32	37	40	46	52	32
	Differential	--	--	3	11	16	45	54	48
6	Common	2	13	22	27	30	42	50	33
	Differential	--	--	3	11	17	54	51	60

### Mechanical Specs

Construction: Plastic case sealed with self-extinguishing resin.

Connections: P = Printed Circuit Pins  $\frac{.03}{(0.65)}$  Square

Dimensions:  $\frac{\text{inches}}{\text{(mm)}}$

